

Mono Perc

Bi-Facial

500Wp-560Wp

2 GW

Manufacturing
Facility



30 Years
Performance
Warranty



12 Years
Manufacturing
Warranty

Product Certifications:

IEC TS 62804-1:2015 | IEC 61701:2011
IS 14286:2010/IEC 61215:2005
IS/IEC 61730(Part I):2004
IS/IEC 61732(Part II):2004



Best in class
thermal coefficients



Sustain heavy
snow & wind loads



Highest
commercial
gains



Split junction
box improve
heat dissipation



Increase
shade
tolerance



Highest
reliability


Corporate Head Office

F27, Amravati MIDC Area,
Express Highway NH 06,
Amravati 444607, Maharashtra.

+91-9146019185
+ 0721-2520922
info@eceindia.com


Corporate Sales Office

2nd Floor, Navle Icon,
Ambegaon, Pune-411046




* All electrical parameters specified at STC: 25°C cell temperature; 1000W/ M² irradiance; AM 1.5

<i>Solar Cells Type</i>	Half cut Mono PERC
<i>Solar Glass</i>	3.2 mm ARC Glass
<i>Length (L)x Width(W) x Height(T)</i>	2278mm x 1134mm x 35mm
<i>Area</i>	2.58 Sqm
<i>Mounting Hole Pitch (Y)</i>	Y1= 1400mm, Y2=1000mm
<i>Mounting Hole Pitch (X)</i>	1093 ± 2 mm
<i>Mounting hole size</i>	14mm*9mm(± 2 mm)
<i>Weight</i>	≈ 28.50Kg
<i>Internal Circuit Connection</i>	Copper Ribbon
<i>Frame</i>	Silver (more than 15 micron) Anodized Aluminium
<i>Cells Encapsulant</i>	EVA (Ethylene Vinyl Acetate)-FC/UFC
<i>Junction Box (Model Type & current Rating)</i>	IP68 Split JB
<i>Connectors</i>	MC4 Compatible
<i>Mechanical Load Condition</i>	Sustain heavy Wind & Snow loads (2400Pa & 5400Pa or 550kg/m2 Maximum diameter of 24mm with hail impact of 83
<i>Cable Length</i>	0.4 Meter



Temperature Coefficients	
Tc of Open Circuit Voltage (β)	-0.3244%/°C±0.02
Tc of Short Circuit Current (α)	0.0518%/°C±0.01
Tc of Power (γ)	-0.3345%/°C±0.02
NOCT	46±2°C



Bi-Facial output - (Back side gain @ STC)		545
15%	Nominal Maximum Power (Pmax) Wp	626.75
	Module efficiency %	24.26
20%	Nominal Maximum Power (Pmax) Wp	654.00
	Module efficiency %	25.32
25%	Nominal Maximum Power (Pmax) Wp	681.25
	Module efficiency %	26.37

Performance warranty

Years	Guaranteed Power (%)
0	100%
17	90%
30	83.75%